


PAL Smart SPME Arrow The Better SPME



Bigger, Smarter, Better - PAL3 Smart SPME Arrow

Bigger surface, faster extraction

More sorption phase, superior sensitivity

Optimized geometry, greater robustness

Full Traceability

Patented



- Each SPME Arrow is equipped with its unique Smart chip containing parameters, ranges and usage history.
- Automatic application of the correct parameters for the individual Smart Arrow.
- Color coded for easy optical identification of coating type and thickness.

PAL3 Smart SPME Arrows - The new dimension for Solid-Phase Micro Extraction

SPME has become one of the most widely used extraction technologies for environmental, food and clinical analyses. It is well suited for automated sample preparation resulting in reduced time per sample, less sample manipulation and solvent consumption. However, the technology remained almost unchanged with some significant drawbacks, such as the limited mechanical stability and small phase volumes of the fibers.

The PAL SPME Arrow is a new patented technology for micro-extraction, combining trace level sensitivity with high mechanical robustness. The PAL SPME Arrow has an outer diameter of 1.1 or 1.5mm, resulting in large sorption phase surfaces and volumes. The arrow-shaped tip allows smooth penetration of vial and injector septa. In contrast to traditional SPME fibers, the Arrow design fully protects the sorptive material, minimizing adverse influences and loss of analytes during transfer processes.

With PAL RTC and PAL RSI the SPME Arrow sampling is fully automated leading to high productivity.



PAL3 Smart SPME Arrow installed in tool.





SPME Arrow Tool

Tool

Liquia Tool

OFF ON

What Better SPME means

Bigger surface,
faster extraction.

More sorption phase,
superior sensitivity.

Optimized geometry,
greater robustness.

2 x higher sample throughput.


Up to 10 x more sensitivity - wider linear range.

PAL SPME Arrows last at least 2 x longer.

Injector septa last at least 2 x longer. Lower running costs.

PAL RTC

= 2 x productivity



Better SPME

- Adaptation of existing SPME methods is straightforward
- PAL SPME Arrow works well for headspace and immersion extraction
- With the wide selection of sorption materials (cf. page 10) a wide variety of compounds are now amenable to SPME
- The PAL SPME Arrow is an ideal field sampling device

PAL SPME Arrow covers a wide range of applications. However, for dynamic headspace applications, especially for volatiles we recommend [ITEX Dynamic Headspace \(DHS\)](#). This powerful technology achieves ng/L sensitivities without the pitfalls of purge & trap systems.

More Volume: Up to 10x more Sensitivity

The table below shows the dimension of a PAL SPME Arrow 1.5 mm (a), 1.1 mm (b) and a SPME Fiber (c) in comparison:





		Sorption phase surface	Sorption phase volume
a		62.8 mm ²	11.8 μL
b		44.0 mm ²	3.8 μL
c		9.4 mm ²	0.6 μL


Table 1: Comparison between Smart SPME Arrows and Smart SPME Fiber

Immersion Extraction: Polyaromatic Hydrocarbons (PAHs) in Water




Extraction yields for water samples containing PAHs @ 50 ng/L after 70 min. A PAL SPME Arrow 20 mm x 250 μm Carbon WR was compared to SPME fiber 10 mm x 100 μm Carbon WR immersion (Kremser et al., 2015).

Headspace Extraction: Aroma Analysis in White Wines



Chromatograms showing the headspace extraction of aroma components from different white wines with PDMS fibers (PAL SPME Arrow 100 µm, 20 x 1.1 mm compared to SPME 100 µm, 10 x 0.3 mm)


Iodoform in Water



Extraction of 1 µg/L iodoform from tap water with DVB fibers (headspace and immersion extraction), PAL SPME Arrow 100 µm, 20 x 1.1 mm compared to SPME 100 µm, 10 x 0.3 mm.


Bigger Surface: 2x Throughput

Immersion Extraction: Polyaromatic Hydrocarbons (PAHs) in Water



Relative immersion extraction yield (measured as % extracted after a 70 min) for PAHs at 50 ng/L with PDMS fibers (PAL SPME Arrow 100 μ m, 20 x 1.1 mm compared to SPME 100 μ m, 10 x 0.3 mm)

Headspace Extraction: Off Flavor Compounds in Water



Relative headspace extraction yield (measured as amount extracted after 30 min) for off-flavor compounds in water at 100 ng/L with DVB fibers. (PAL SPME Arrow 100 μ m, 20 x 1.1 mm compared to SPME 100 μ m, 10 x 0.3 mm)

References

- [1] Belardi R., Pawliszyn J., Water Pollut. Res.J.Can. 1989, 24, 179
- [2] [SPME Arrow - Evaluation of a Novel Solid-Phase Microextraction Device for Freely Dissolved PAHs in Water; Kremser A. et al., Anal. Bioanal. Chem. 2016, 408, 943-952](#)
- [3] Solid phase microextraction Arrow for the sampling of volatile amines in wastewater and atmosphere; Helin A. Et al., J. Chrom. A 2015, in press
- [4] PAL System Application Notes: Determination of iodoform in drinking water by SPME and GC/MS and Determination of C2-C12 aldehydes by SPME on-fiber derivatization and GCMS

With the PAL RTC and PAL RSI the entire SPME process is fully automated guaranteeing process safety and high reproducibility.



PAL Heatex Stirrer - New Mixing and Heating Technology for Sample Preparation and SPME.

The powerful PAL Heatex Stirrer mixes samples rapidly applying cycloid shaped mixing patterns without the need for stir bars. For SPME headspace and immersion sampling the special design (pat. pending) ensures optimal performance.

The PAL Heatex Stirrer offers:

- Rapid equilibration through effective stirring for headspace and immersion SPME sampling while ensuring the integrity of the fiber
- Efficient dissolution of solids, temperature controlled
- Thorough liquid/liquid extraction
- Stirring/heating for derivatization reactions
- No stir bar required, constant stirring also with samples containing solids
- No cross contamination
- Precise control of the equilibration temperature 40-150 °C
- Software controlled, temperature and stirring speed are logged

PAL Smart SPME Arrow Ordering Information

System requirements

- PAL RTC or RSI with firmware 2.3 or higher
- PAL SPME Arrow Tool
- PAL Agitator & Heatex Stirrer Module
- Adaptation of GC-injector (see page 11)
- A PAL SPME Arrow Conditioning Module is highly recommended, the PAL SPME Fiber Conditioning Module cannot be used with SPME Arrow.

The PAL Smart SPME Arrows are available in order quantities of one, three or five Smart SPME Arrows per box.

For method development, a set of each fiber type (set of five) is available.




No.	Outer Diameter	Phase Thickness	Color Code	Set of 1 Smart SPME Arrow Description PNo.	Set of 3 Smart SPME Arrow Description PNo.	Set of 5 Smart SPME Arrow Description PNo.
PDMS Smart SPME Arrow (Polydimethylsiloxane)						
1	1.1 mm	100 µm	Red	SARR11-P-100/20-P1	SARR11-P-100/20-P3	SARR11-P-100/20-P5
2*	1.5 mm	100 µm	Red	SARR15-P-100/20-P1	SARR15-P-100/20-P3	SARR15-P-100/20-P5
Polyacrylate Smart SPME Arrow						
3	1.1 mm	100 µm	Gray	SARR11-A-100/20-P1	SARR11-A-100/20-P3	SARR11-A-100/20-P5
Carbon WR / PDMS Smart SPME Arrow (Carbon Wide Range / Polydimethylsiloxane)						
4	1.1 mm	120 µm	Light Blue	SARR11-C-WR-120/20-P1	SARR11-C-WR-120/20-P3	SARR11-C-WR-120/20-P5
5*	1.5 mm	120 µm	Light Blue	SARR15-C-WR-120/20-P1	SARR15-C-WR-120/20-P3	SARR15-C-WR-120/20-P5
DVB / PDMS Smart SPME Arrow (Divinylbenzene / Polydimethylsiloxane)						
6	1.1 mm	120 µm	Violet	SARR11-DVB-120/20-P1	SARR11-DVB-120/20-P3	SARR11-DVB-120/20-P5
7*	1.5 mm	120 µm	Violet	SARR15-DVB-120/20-P1	SARR15-DVB-120/20-P3	SARR15-DVB-120/20-P5
DVB / Carbon WR / PDMS Smart SPME Arrow (Divinylbenzene / Polydimethylsiloxane / Carbon Wide Range)						
8	1.1 mm	120 µm	Dark Gray	SARR11-DVB/CWR120/20-P1	SARR11-DVB/CWR120/20-P3	SARR11-DVB/CWR120/20-P5
9*	1.5 mm	120 µm	Dark Gray	SARR15-DVB/CWR120/20-P1	SARR15-DVB/CWR120/20-P3	SARR15-DVB/CWR120/20-P5
PDMS Smart SPME Arrow (Polydimethylsiloxane)						
10	1.5 mm	250 µm	Black	SARR15-P-250/20-P1	SARR15-P-250/20-P3	SARR15-P-250/20-P5
Smart SPME Arrow Selection for method development (set of 5 different Smart SPME Arrow types)						
Smart SPME Arrow Selection of 5 Smart SPME Arrow standard types No. 1, 3, 4, 6 and 8						SARR1115-SEL5-S2

* Smart SPME Arrow wide types - for use with solvents or reagents, that may lead to moderate swelling of PDMS phases.


Table 2. PAL Smart SPME Arrow Order Information.

All Smart SPME Arrows have a phase length of 20 mm. Smart SPME Arrow cannot be used with standard SSL injectors of most GC manufactures. The use of the specific Smart SPME Arrow Adaptation Kit is mandatory. Liners in the injector must be selected to fit Smart SPME Arrows with 1.1 mm or 1.5 mm diameter. Please see the list of available kits at the end of this document. The Smart SPME Arrow assortment and the range of applications will be constantly expanded and developed.

Ordering information for required parts

<p>SPME Arrow Starter Kit (injector specific)</p> <p>PNo.: see below</p>		<p>Starter Kit containing</p> <ul style="list-style-type: none"> – SPME Arrow Tool – Smart SPME Arrow Selection of five different Smart SPME Arrows – Smart SPME Arrow Instruction Leaflet – Adapter Kit for GC injector (details see below)
<p>Heatex Stirrer Module</p> <p>PNo.: PAL3-HeatexStirrer</p>		<p>For mixing and heating in sample prep and SPME Arrow</p> <ul style="list-style-type: none"> – Temperature range ambient temperature - 150 °C – Mixing speed up to 1600 rpm (200 cycloidal loops) – Optimized for 20 mL vials (for 10 mL vials a special adapter is required)
<p>Agitator Module</p> <p>PNo.: PAL3-Agitator</p>		<p>The Agitator Module provides 6 positions for 20 mL vials for incubation and agitation of samples.</p> <ul style="list-style-type: none"> – Temperature range ambient temperature – 200 °C – Agitation speed 250 – 750 rpm – Optional adapters for 2 mL or 10 mL vials

Ordering information for optional modules

<p>SPME Arrow Conditioning Module</p> <p>PNo.: PAL3-SPME-ArrowCond</p>		<p>For the conditioning of SPME Arrow as well as SPME fibers prior to sample enrichment</p> <ul style="list-style-type: none"> – Position for automated conditioning – Position for manual pre-conditioning – Automated purge gas valve – Manual gas valve for pre-conditioning – Replacement liners for easy maintenance
---	--	--

Ordering information for starter kits and suitable liners

Starter Kits	PAL3-SARR-Start-GC2010	Starter Kit SPME Arrow for Shimadzu GC-2010 Plus consisting of: 1 Adaption Kit for the split/splitless injector of Shimadzu GC-2010 Plus (ARR-SSL-Inj-GC2010), 1 Liner Nut, 1 Screw Cap, 2 SPME Arrow Liner, 1 SPME Arrow Tool Kit (PAL3-SPME-Arrow-Kit)
	PAL3-SARR-Start-GC6890	Starter Kit SPME Arrow for Agilent GC6890 consisting of: 1 Adaption Kit for the split/splitless injector of Agilent GC 6890 (ARR-SSL-Inj-GC6890), 2 SPME Arrow Liners for SSL Injector of the Agilent GC 6890, 1 SPME Arrow Tool Kit (PAL3-SPME-Arrow-Kit)
	PAL3-SARR-Start-GC7890	Starter Kit SPME Arrow for Agilent GC 7890 consisting of: 1 Adaption Kit for the split/splitless injector of Agilent GC 7890 (ARR-SSL-Inj-GC7890), 2 SPME Arrow Liners for SSL Injector of the Agilent GC 7890, 1 SPME Arrow Tool Kit (PAL3-SPME-Arrow-Kit)
	PAL3-SARR-Start-Tr1300	Starter Kit SPME Arrow for Thermo GC Trace 1300/1310 consisting of: 1 Adaptation Kit for the split/splitless injector of Thermo GC Trace1300/1310 (ARR-SSL-Inj-Trace1300), 2 SPME Arrow Liners for SSL Injector of Thermo GC Trace1300/1310, 1 SPME Arrow Tool Kit (PAL3-SPME-Arrow-Kit)
	PAL3-SARR-Start-TrUltra	Starter Kit SPME Arrow for Thermo GC Trace Ultra consisting of: 1 Adaptation Kit for the split/splitless injector of Thermo GC TraceUltra (ARR-SSL-Inj-TraceUltra), 2 SPME Arrow Liners for SSL Injector of Thermo GC TraceUltra, 1 SPME Arrow Tool Kit (PAL3-SPME-Arrow-Kit)
Suitable Liners	ARR-Liner-CondModule	Liner for SPME Arrow Conditioning Module, package containing 3 pcs
	ARR-Liner-GC2010	SPME Arrow Liner for SSL Injector of SHIMADZU GC-2010 Plus, package containing 3 pcs
	ARR-Liner-GC6890	SPME Arrow Liner for SSL Injector of AGILENT GC 6890, package containing 3 pcs
	ARR-Liner-GC7890	SPME Arrow Liner for SSL Injector of AGILENT GC 7890, package containing 3 pcs
	ARR-Liner-Trace1300	SPME Arrow Liner for SSL Injector of Thermo GC Trace1300, package containing 3 pcs
	ARR-Liner-TraceUltra	SPME Arrow Liner for SSL Injector of Thermo GC TraceUltra, package containing 3 pcs

PAL SYSTEM

Ingenious sample handling



Distributed by:

For more information on the PAL System visit:

www.palsystem.com



PAL is a registered trademark of CTC Analytics AG, Switzerland