

## Application News

# No. 082

### Total Organic Carbon Analysis

## TOC System Suitability Test Using TOC-1000e According to USP 643

For water used in pharmaceuticals, the US Pharmacopoeia (USP) specifies that total organic carbon (TOC) should be used for management of organic impurities. According to USP 643 TOC, TOC analyzers to be used for analysis of bulk purified water and water for injection must satisfy the TOC system suitability test using test water with a carbon content of 0.500 mg/L.

This article introduces an actual example of TOC system suitability testing using the online total organic carbon analyzer TOC-1000e and optional sampler.

M. Tanaka



Fig. 1 TOC-1000e + Sampler

### ■ Summary of USP 643 TOC System Suitability Test

The USP 643 TOC system suitability test for bulk purified water and water for injection specifies the use of two USP reference standards (sucrose and 1,4-benzoquinone) with a carbon content of 0.500 mgC/L. Sucrose is used as the standard solution, and 1,4-benzoquinone as the system suitability solution. The test procedure is shown in Table 1.

Table 1 TOC System Suitability Test Procedure in Accordance with USP 643


- (1) Measure TOC of reagent water (pure water used for preparation of the standard solution) →  $r_w$ .
- (2) Measure TOC of sucrose standard solution (0.500 mg/L of carbon) →  $r_s$ .
- (3) Measure TOC of system suitability solution (1,4-benzoquinone solution with a carbon content of 0.500 mg/L) →  $r_{ss}$ .
- (4) System suitability is satisfied if  $100 (r_{ss} - r_w) / (r_s - r_w)$  is 85% - 115%.

### Test Procedure


TOC-1000e is equipped with the USP's TOC system suitability test software.

The test procedure is as follows:


1. On [Validation] screen, Check [5. SYSTEM SUITABILITY] and press [Start] button.




2. Set the range to 500 ppb in [Cal Range], and set the measurement frequency in [Repetition].



3. Follow the on-screen instructions to set the reagent for USP testing using TOC-1000e, including reagent water, benzoquinone solution and sucrose solution to the sampler, and press [Check] button.



4. When the measurement is completed, the results are shown in [Result]. If the results satisfy the standard values, [Pass] is displayed.



### Test Results


Using TOC-1000e, a TOC system suitability test was conducted. The measurement conditions are shown in Table 2. Table 3 shows the measurement results and Fig. 2 shows an example of printed results. The results of tests repeated three times satisfied the specified values (85 – 115%).

**Table 2 Measurement Conditions**

Analyzer	: Shimadzu TOC-1000e online total organic carbon analyzer
Calibration curve	: 0-250-500 ppb
Reagents	: USP 643 system suitability test set, confirmed (USP standard) 500 ppb sucrose 500 ppb 1,4-benzoquinone reagent water

**Table 3 Results of TOC System Sustainability Test**

	Blank [ppb]	Sucrose [ppb]	Benzoquinone [ppb]	Result
1	23.0	509	526	103.5 %
2	21.3	516	509	98.6 %
3	20.9	514	514	100.0 %



**Fig. 2 Results of TOC System Sustainability Test**

### Conclusion

A TOC system suitability test can be conducted easily by TOC-1000e using the optional sampler and following the instructions on the software screen.



Shimadzu Corporation

www.shimadzu.com/an/

**For Research Use Only. Not for use in diagnostic procedures.**

This publication may contain references to products that are not available in your country. Please contact us to check the availability of these products in your country.

The content of this publication shall not be reproduced, altered or sold for any commercial purpose without the written approval of Shimadzu. Shimadzu disclaims any proprietary interest in trademarks and trade names used in this publication other than its own. See <http://www.shimadzu.com/about/trademarks/index.html> for details.

The information contained herein is provided to you "as is" without warranty of any kind including without limitation warranties as to its accuracy or completeness. Shimadzu does not assume any responsibility or liability for any damage, whether direct or indirect, relating to the use of this publication. This publication is based upon the information available to Shimadzu on or before the date of publication, and subject to change without notice.